



## Guest / Side / Stacking Chair Disassembly



- 1 Tools Required: **Indy**  
Phillips Head Screwdriver, Flat Head Screwdriver, Needle Nose Pliers, Staple Puller
- 2 The back rest is press fitted to the steel frame. Using the hammer, strike the back rest with an upwards motion until it separates from the steel frame. If applicable, use the phillips head screwdriver to remove the 4 screws that attach the upholstered pad to the back rest.



- 3 The 1-piece plastic seat is press fitted to the steel frame. remove the seat upwards and away from the steel frame. If applicable, use the phillips head screwdriver to remove the 4 screws that attach the upholstered pad to the seat.





- 4 Remove the 4 plastic glides from the bottom of the steel frame.



We strive to use North American (non-imported) components in our manufacturing process  
Proudly Manufactured in Western New York!



CHAIRS THAT FIT EVERY TASK - FOR EVERY BODY		"BUILT IN AMERICA WITH QUALITY NORTH AMERICAN MADE COMPONENT PARTS" SEATING SERIES 275 STANDARD FIT 350 INTENSIVE USE & HEAVY DUTY 550 GENEROUS FIT	
PO Box 898   60 N. State Street   Nunda, New York 14517   800.46 8.247 5   F 585.468.2804   sales@seatinginc.com   www.seatinginc.co m			

## Guest / Side / Stacking Chair Disassembly



5 If applicable, The upholstered back and/or seat pad are stapled to plastic substructures. Using the staple puller, remove the staples.



6 The upholstery is glued to the foam cushions. The foam cushions are glued to the plastic substructures. Pull the upholstery away from the foam cushions. Pull the foam cushions away from the plastic substructures while using a flat head screwdriver or the staple puller to assist the release.



- |   |                       |                           |
|---|-----------------------|---------------------------|
| 7 | Parts List:           | Composition:              |
|   | 1 Back Rest           | Plastic                   |
|   | 1 Seat                | Plastic                   |
|   | 1 Metal Frame         | ♻️Steel                   |
|   | 4 Glides              | Plastic                   |
|   | If Applicable:        |                           |
|   | 1-2 Substructures     | Plastic                   |
|   | 1-2 Cushions          | Foam                      |
|   | 1-2 Upholstery Pieces | Fabric, Vinyl, or Leather |
|   | 4-8 Screws            | ♻️Steel                   |
|   | Staples               | ♻️Steel                   |

We strive to use North American (non-imported) components in our manufacturing process  
Proudly Manufactured in Western New York!

